

High-pressure Ultra Clean unit

HPE-300-250-50-C3-M2

Common features:

- Complete skid for equipment mounting
- Extra heavy-duty chassis with steering swivel
- Water pre-charge booster pump
- Water tank with minimum level sensor
- Inlet water temperature sensor
- Inlet water pressure sensor
- Three-stage water filtration (300-10-5 µm)
- Electrical panel with LED controls and emergency button
- Maximum pressure safety device with calibrated rupture disc
- Ultra-high pressure gauge (4000 bar series)
- Ultra-high pressure bypass with remote pneumatic control
- Ultra-rotating manual gun with 4-jet head
- High-pressure hose set total length 10 m



Technical Specifications HPE 300-50-C3-M2:

Max pressure:	3000 bar (funz. continuato)
Max flow rate:	7 lt/min
Electric motor:	50 hp (37 kw)
Water tank:	300 L
Skid dimensions:	3100 x 1100 x h 1810 mm

Optional:

- electrical panel with inverter for precise control of working pressures and digital display of values on the panel (Model C7: Skid dimensions 3100 x 1100 x H 1810 mm)

Technical Specifications HPE 250-50-C3-M2:

Max pressure:	2450 bar (funz. continuato)
Max flow rate:	10 lt/min
Electric motor:	60 hp (44 kw)
Water tank:	300 L
Skid dimensions:	3100 x 1100 x h 1810 mm

Optional:

- electrical panel with inverter for precise control of working pressures and digital display of values on the panel (Model C7: Skid dimensions 3100 x 1100 x H 1810 mm)