

High-pressure Ultra Clean unit

HPE-300-250-50-S5

Common features:

- Complete skid for equipment mounting
- Water pre-charge booster pump
- Water tank with low-water level sensor
- Inlet water temperature sensor
- Inlet water pressure sensor
- Three-stage water filtration (300-10-5 µm)
- Electrical panel with LED controls and emergency stop button
- Maximum water pressure safety device with calibrated rupture disc
- High-pressure gauge 4000 bar series
- High-pressure bypass with pneumatic remote control



Technical specifications HPE 300-50-S5-M2:

Max pressure:	3000 bar (continuous operation)
Max flow rate:	7 l/min
Electric motor:	50 hp (37 kW)
Water tank:	300 l
Skid dimensions:	2400 x 1000 x h 1370 mm

Optional:

- electrical control panel with inverter for precise control of working pressures and digital display of values on the panel
(Model S7: skid dimensions 2600 x 1000 x 1385 mm)

Technical specifications HPE 250-50-S5-M2:

Max pressure:	2450 bar (continuous operation)
Max flow rate:	10 lt/min
Electric motor:	60 cv (44 kw)
Water tank:	300 lt
Skid dimensions:	2400 x 1000 x h 1370 mm

Optional:

- electrical control panel with inverter for precise control of working pressures and digital display of values on the panel
(Model S7: skid dimensions 2600 x 1000 x 1385 mm)